



48 VOLT WITH AC SYSTEM

AGM OR LI BATTERIES

145/70 R12 ALUMINUM RIMS

LED LIGHTS WITH DRL FUNCTION

HYDRAULIC BRAKES ON 4
WHEELS + HANDBRAKE

ITALCAR INDUSTRIAL SRL | Via Bruino, 36 | 10040 Rivalta di Torino (TO)
Tel. +39 011 9040225 | Fax +39 011 9032986 | info@italcar.com | www.italcar.com










nev

C2S.5	
C25.5	
	ITALCAR an Italian Brand

places:	2
batteries:	AGM pack or LI pack
motor:	AC - 48v
controller:	AC – 450A
transmission:	rear axle, ratio 12,49:1
steering:	self compensating single reduction rack and pignon
performances: max speed: range: max hill climbing ability:	45 km/h (L6e) – 55km/h (L7e) 80 km 20%
dimensions:	
overall	2030mm x 1280mm x 1620mm
ground clearance (empty):	120mm
turning radius:	3,5 mt
chassis:	galvanized steel frame and powder coated
body:	PP impregnated and painted
suspensions:	
front	Independent suspensions
rear	leaf springs with hydraulic shock absorbers
brakes:	automotive types, double hydraulic circuit on four wheel with hand brake
front	disc
rear	drum
tyres: reccomended pressure:	145 / 70 – 12 with aluminum rims 2,5 bar (25kPa)
carica batterie:	in dotazione al veicolo, 220/230V
basic configuration:	doors, 3 points safety belts, glass windshield, front & rear lights and turning lights, reverse buzzer, folding rearview mirrors, rear trunk with key lock, 12v socket, wiper and washing system, HI-FI (radio + speakers), heating system
optional	whole glass doors

All above specification were correct at the time of the printing and are considerated indicatives and not binding. ITALCAR INDUSTRIAL S.r.l. maintains the right to bring any changes without notice







seguici su - follow us on



