

MODEL: HAULER PRO

TYPE: ELECTRIC 72V POWERED TRUCK

MODEL YEAR: 2017

Part No: 651395



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

- Solid State continuously variable AC speed controller
- Seatwrap mounted direction selector switch (Forward-Neutral-Reverse)
- Anti-roll back, walkaway braking and alarm
- Anti-stall motor protection
- Regenerative 'Pedal Down' and/or 'Pedal Up' braking

- Full torque, reduced speed reverse
- Inductive throttle sensor
- Diagnostic indicator
- Factory programmable to application

Battery Charger: 900 Watt, 72 VDC, 120/230 VAC 50/60 Hz. Underwriters Laboratories (U.L.) Listed, (C.S.A. Certified)

Motor: 72 Volt AC Induction, solid copper windings. Non vented 22.4 hp (16.7 kW) Peak.

Drive Train: Direct motor shaft connected to transaxle pinion shaft

Electrical System: 72 Volt DC, nine, 8 volt deep cycle storage batteries (78 minutes @ 75 Amps, 170 amp-hour @ 20 hr. discharge rate)

Transaxle: Differential with helical gears

Brakes: Dual rear wheel mechanical self-adjusting drum brakes. Automatic single point park brake release with self-compensating system.

Cargo Bed: Roto-molded cross-linked polyethylene. Lifts for access to powertrain. Removable hinged multi-position tailgate with cam over latch mechanism.

Cargo Bed. Roto-moided		OVERVIEW	9	i multi-position taligate with carn over laten mechanism.			
Dimensions		Performance					
Overall Length	115.0 in (292.10 cm)	Seating Capacity	y	2 Person			
Overall Width	49.4 in (125.48 cm)	Dry Weight		910 lb (412.77 kg) (Without Batteries)			
Overall Height (No Canopy)	47.3 in (120.14 cm) (Top of steering wheel)	Curb Weight		1475 lb (669.05 kg)			
Overall Height (With Canopy)	70.5 in (179.07 cm)	Bed Load Capacity		800 lb (362.87 kg)			
Wheel Base	76.0 in (193.04)	Vehicle Load Capacity		1200 lb (544.31 kg)			
Front Wheel Track	35.0 in (88.90 cm)	Outside Clearance Circle		21.5 ft (6.55 m)			
Rear Wheel Track	38.5 in (97.79 cm)	Intersecting Aisle Clearance N/A					
Ground Clearance (at Differential)	4.5 in (11.43 cm)	Speed (Level Ground)		14.5 mph \pm 0.5 mph (23.34 kph \pm 0.80 kph)			
Cargo Box Width (inside)	44.0 in (111.76 cm)	Maximum Drawbar		1262 lb (5614 N)			
Cargo Box Length (inside)	39.0 in (99.06 cm)	Towing Capacity		1500 lb (680.39 kg) max load			
Cargo Box Depth (inside)	12.0\ in (30.48 cm)	Steering & Sus	pension				
Cargo Box Capacity	12 cu ft (0.34 cu m)	Steering		Self-compensating rack and pinion			
Cargo Box material	Roto-molded polyethylene	Front Suspension		Leaf springs with hydraulic shock absorbers			
Vehicle Power		Rear Suspension		Leaf springs with hydraulic shock absorbers			
Power Source	72 Volts DC	Service Brake		Rear wheel mechanical self-adjusting drum			
Motor Type	AC Induction	Parking Brake		Self-compensating, single point engagement			
Horsepower (kW)	22.4 hp (16.7 kW) Peak	Front & Rear Tires		K500 18 x 8.5 - 8 (6 Ply), Black Wheel			
Electrical System	72 Volt	Body & Chassis					
Batteries (Qty, Type)	Nine, 8 Volt Deep Cycle	Frame		Welded steel. DuraShield™ powder coat			
Key or Pedal Start	Pedal Start	Front Body & Finish		Injection Molded TPO			
Battery Charger	900 Watt, 72VDC	Standard Color		Forest Green			
Speed Controller	350 Amp AC	Noise & Vibration					
Drive Train	Motor Shaft Direct Drive	Noise Sound p		ressure; continued A-weighted ≤ 70 db(A)			
Transaxle	Differential with helical gears	Vibration, WBV Highest		RMS value of weighted acceleration is less than 2.5 m/s $$			
Gear Selection	Forward-Neutral-Reverse	Vibration, HAV Highest		RMS value of weighted acceleration is less than 2.5 m/s			
Rear Axle Ratio	17:1		The unce	ertainty of measurement is 0.12 m/s			
	Measurement methods were applied per the ISO 2631 and ISO 5349						
Some items shown may be optional equipment		standards under conditions of typical vehicle surfaces.					



TAL	LED) A (CCESSORIES (Installation not included)*			
Std	Opt	Fld	Item	Std	Opt	Fld
ota	Орт	i iu			Орт	ıια
1	х				Х	
	^					
TURF TIRES: K500 18 x 8.5 - 8 (6 Ply), Black Wheel X						
+^	Х				Х	
	х			х	ļ ,	-
					Х	
						-
					_	
Х				х		
+^	х				Х	-
					-	-
	^					
X						
+^	χ				_	
	^					
X						Х
+^	У					Х
	^					Х
X						Х
+^	Х					
						Х
						Х
						Х
X						Х
+^	х					Х
						Х
						Х
						L I
х						Х
						Х
						Х
+^	Y					Х
		\dashv				Х
У	^	\dashv				X
	Y	\dashv				Х
						Х
-		\exists			J	
1		\dashv			1	Х
Y	^	\exists				Х
^	У	\exists				X
		\dashv	IVIIITO - O LATICI		l	_^
		\dashv				
		X	X	State of Charge Meter 1	Std Opt Ftd State of Charge Meter	Std Opt Ftd State of Charge Meter