



**attiva 4LC.5**



48 VOLT CON SISTEMA AC

8 X 6V BATTERIE PB/ACIDO

205/50-10 CON CERCHI IN  
ALLUMINIO

LUCI ANTERIORI E POSTERIORI


FRENI IDRAULICI SULLE 4  
RUOTE + FRENO A MANO

**ITALCAR INDUSTRIAL SRL** | Via Bruino, 36 | 10040 Rivalta di Torino (TO)  
Tel. +39 011 9040225 | Fax +39 011 9032986 | [info@italcar.com](mailto:info@italcar.com) | [www.italcar.com](http://www.italcar.com)



## attiva 4LC.5

posti:	4
batterie:	8 x 6V, US2200 standard
motore:	AC 48V – Mahle Letrika
controllo:	sevcon GEN4 – AC – 450A
trasmissione:	trazione posteriore, 19 denti, ratio 12,31:1
sterzo:	a cremagliera di tipo automobilistico
prestazioni:	
velocità massima suggerita	30 km/h
autonomia	80 km
pendenza superabile (max)	15% (20% con rapporto optional 16:1)
dimensioni:	
veicolo	4400mm x 1200mm x 1800mm
dimensioni:	
Cassone	1830mm x 1100mm x 240mm
altezza da terra (a vuoto):	250mm
raggio di sterzata:	5,1 mt
interasse	3200mm
telaio:	in acciaio galvanizzato con verniciatura a polvere
carrozzeria:	PP impregnato e verniciato
sospensioni:	
anteriori	sospensioni indipendenti
posteriori	balestre con ammortizzatori idraulici
freni:	ad azionamento idraulico sulle 4 ruote con circuito sdoppiato
anteriori	disco
posteriori	tamburo
pneumatici:	205 / 50 – 10 con cerchione di alluminio
pressione di gonfiaggio:	1,7 bar (25psi)
carica batterie:	in dotazione al veicolo - 48v, 220/230V
dotazioni di serie:	include: avvisatore acustico di retromarcia, cruscotto digitale, luci anteriori e posteriori, clacson, indicatori di direzione, specchietti retrovisori laterali, parabrezza in plexiglass



ITALCAR è un marchio Italiano



clicca mi piace - like us on



seguici su - follow us on



Tutti i dati riportati sono indicativi e non vincolanti  
la ITALCAR INDUSTRIAL S.r.l. si riserva il diritto di apportarvi qualsiasi variazione senza alcun preavviso



**attiva 4LC.5**



48 VOLT WITH AC SYSTEM

8 X 6V LEAD-ACID BATTERIES

205/50-10 ALUMINUM RIMS

FRONT & REAR LIGHTS

HYDRAULIC BRAKES ON 4  
WHEELS + HANDBRAKE

**ITALCAR INDUSTRIAL SRL** | Via Bruino, 36 | 10040 Rivalta di Torino (TO)  
Tel. +39 011 9040225 | Fax +39 011 9032986 | [info@italcar.com](mailto:info@italcar.com) | [www.italcar.com](http://www.italcar.com)



ITALCAR an Italian Brand



# attiva 4LC.5

places:	4
batteries:	8 x 6V, US2200 standard
motor:	AC 48V – Mahle Letrika
controller:	sevcon GEN4 – AC – 450A
transmission:	rear axle, 19 spline, ratio 12,31:1
steering:	self compensating single reduction rack and pignon
performances:	
suggested max speed	30 km/h
range	80 km
max hill climbing ability	15%(20% with optional ratio 16:1)
vehicle dimensions:	
overall	4400mm x 1200mm x 1800mm
cargo dimensions:	
overall	1830mm x 1100mm x 240mm
ground clearance (empty):	250mm
turning radius (min):	5,1 mt
wheel base	3200mm
chassis:	galvanized steel frame and powder coated
body:	PP impregnated and painted
suspensions:	
front	Independent suspensions
rear	leaf springs with hydraulic shock absorbers
brakes:	automotive types, double hydraulic circuit on four wheel with hand brake
front	Disc
rear	drum
tyres:	205 / 50 – 10 with aluminium rims
recommended pressure:	1,7 bar (25psi)
battery charger:	included with the vehicle - 48v, 220/230V
basic configuration:	Includes: reverse buzzer; digital speedometer, front and rear lights, horn, direction indicators, rear-view mirrors, one piece plexiglass

All above specification were correct at the time of the printing and are considered indicatives and not binding. ITALCAR INDUSTRIAL S.r.l. maintains the right to bring any changes without notice

clicca mi piace - like us on



segui su - follow us on

